



PROJECT	
DWG #	
ITEM #	

SUGGESTED SPECIFICATION

Insulate per ADA 4.19.4 and or ICC all exposed lavatories drain piping, hot/cold stops and supplies. Protectors shall conform to UPC/IAPMO PS 94-2001A. Protectors will consist of one-piece universal fit jacket with smooth and soft texture, anti-fungal, anti-microbial, closed cell PVC with heat welded construction. Insulation shall conform to International Building Code (IBC) with testing standard of ASTM E84-07 Class A Material (25 Flame/450 Smoke) criteria. Protectors shall consist of a dual fastening system of full length *VelcroFastening Strips and tamper resistant self-locking snap fasteners. Shall have PVC Velcro fasteners adhered with heat weld bonding to allow for custom trimming. Protectors must be secured by Heavy-Duty, Self-Locking, Snap Fasteners for permanent safe fit option to deter theft and/or injury.

Manufacturer: Plumberex, Inc. Handy Shield™ and shall consist of all the above listed components and features.

*Velcro is a registered trademark of Velcro USA Inc.

PRODUCT DETAIL:

For kitchen sink applications, specifically waste disposal, exposed piping and supply stop protectors requiring compliance with ADA 4.24. Waste disposal, bend and P-Trap covers attach by a dual fastening system of a ¾" full length Velcro* strip and tamper resistant, self-locking snap fasteners. Surfaces are easy to clean non-absorbent PVC with U/V inhibited, antifungal/antimicrobial agents.

PART NUMBER BY PRODUCT

☐ **MODEL # 3071WD-P37**
White

Waste Disposal Cover/Bend
Cover and P-Trap Cover
Fits Pro-333/SS/777 Series

Other Handy-Shield™ color options:



Waste Disposal w/Bend & P-Trap Cover Fits Pro-333/SS/777 Series

